



Confirmation of Product Type Approval

Company Name: EPMAR CORPORATION

Address: 9930 PAINTER AVE. WHITTIER CA 90605 United States

Product: Deck Coverings

Model(s): Syndeck Super Underlayment Sealer SS1259

Endorsements:

Certificate Type	Certificate Number	Issue Date	Expiry Date
Product Design Assessment (PDA)	24-0114774-PDA	24-OCT-2024	23-OCT-2029
Manufacturing Assessment (MA)	20-LA4092731	17-JAN-2020	16-JAN-2025
Product Quality Assurance (PQA)	NA	NA	NA

Tier

3 - Type Approved, unit certification not required

Intended Service

Marine & Offshore Applications - Primary Deck Covering and Floor Covering for Ships and Offshore Facilities.

Description

SynDeck® Super Underlayment Sealer SS1259 is a clear marine epoxy underlayment sealer. It is a high thixotropic two-component epoxy specifically designed to seal underlayments, decks, floors and other surfaces. The material is designed for use over underlayment and other surfaces where high porosity is a concern.

SynDeck Super Underlayment Sealer SS1259 is ideal for sealing Syndeck underlayments such as: SynDeck Ultra Lightweight Underlayment SS1290FC, SynDeck Ultra Lightweight Terrazzo SS1290FCT and SynDeck 1.5 IMO Underlayment SS1295.

Ratings

Material is not readily ignitable and meets low flame spread requirements for primary deck covering and floor covering as specified in Part 5 of Annex 1 of the IMO FTP Code 2010 (Res. MSC.307(88)). Product meets Part 2 of Annex 1 without further testing by complying with paragraph 2.7 in appendix 4 of Annex 1: Part 5 of the IMO FTP Code 2010. Material is deemed not capable of producing excessive quantities of smoke or toxic products.

Service Restrictions

1. Unit Certification is not required for this product. If the manufacturer or purchaser requests an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.

2. The scope of Type Approval is to comply with MSC.1/Circ.1221 dated 11 December 2006.

3. The product is approved for application to any metallic substrate having a thickness higher than 3 mm.
4. The thickness of the application shall not exceed 10 mils (0.25 mm) for use as a floor covering from a flammability and smoke generation stand point.
5. Two component epoxy to be installed per manufacturer instructions.
6. If any adhesive is used other than the one used during testing, then that adhesive has to be tested for low flame spread characteristics according to IMO 2010 FTP Code Part 5.

Comments

1. The Manufacturer has provided a declaration about the control of, or the lack of, Asbestos in this product.
2. Production items are to be manufactured in accordance with a quality control system which shall be maintained to ensure that items are of the same standard as per tested/approved prototype.
3. Production item should be installed/used in accordance with manufacturer's instructions.
4. Unless specially directed by Administration, this approval is not to be construed as a substitute for Flag Administration's approval for the purpose of SOLAS/IMO MODU Code, as amended.
5. This assessment has not been performed on behalf of any flag administration.
6. For use on US or EC flagged vessels, please use the equivalent USCG or EC/EMSA MED approval(s).
7. Individual review to the intended use on specific vessel, MODU or facility is required.

Notes, Drawings and Documentation

Southwest Research Institute (SwRI) Test Report No. 01.23236.18.321 [Material 3], dated 13 June 2018.
Follow-up Document: SwRI® Test Report No.: 01.25555.02.156-230110, Report Date: March 14, 2024.

Term of Validity

This Product Design Assessment (PDA) Certificate remains valid until 23/Oct/2029 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

ABS Rules

ABS Rules for Conditions of Classification, Part 1A (2024): 1A-1-4/7.7, 1A-1-A3 and A4, which covers the following:

2024 ABS Marine Vessel Rules 3-4-1

ABS Rules for Conditions of Classification – Offshore Units and Structures, Part 1B (2024): 1B-1-4/9.7, 1B-1-A2 and A3, which covers the following:

2024 ABS Mobile Offshore Units Rules 5-1-1 / 3.5; 5-1-1 / 5.17; 5-1-1 / 5.21; 5-1-1 / 5.23.

International Standards

2010 IMO FTP Code - Resolution MSC.307(88), 2012 Edition (enter into force 1 July 2012) Parts 2 & 5 of Annex 1.

EU-MED Standards

NA

National Standards

NA

Government Standards

USCG Certificate of Approval 164.117/59/0, issued 1 March 2024, expires 1 March 2029 as a Floor Finish (SOLAS); USCG Certificate of Approval 164.106/59/0, issued 1 March 2024, expires 1 March 2029 as a Primary Deck Covering (IMO).

The product complies with the following sections of the Canadian Vessel Fire Safety Regulations: 224, 225, and 327(1)(b) and 327(3)(b) and products are approved on behalf of the Minister of Transport (Transport Canada) in accordance with TP14612, when manufactured at a facility with an ABS manufacturing assessment (MA).

Other Standards

NA



Corporate ABS Programs
American Bureau of Shipping
Print Date and Time: 15-Jan-2025 1:28

ABS has used due diligence in the preparation of this certificate, and it represents the information on the product in the ABS Records as of the date and time the certificate is printed.

If the Rules and/or standards used in the PDA evaluation are revised or if there is a design modification (whichever occurs first), a PDA revalidation may be necessary.

The continued validity of the MA is dependent on completion of satisfactory audits as required by the ABS Rules. The validity of both PDA and MA entitles the product to receive a **Confirmation of Product Type Approval**.

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or prior to the effective date of the ABS Rules and standards applied at the time of PDA issuance. ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. The manufacturer is responsible to maintain compliance with all specifications applicable to the product design assessment. Unless specifically indicated in the description of the product, certification under type approval does not waive requirements for witnessed inspection or additional survey for product use on a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.