

SYSTEM GUIDE

NuFlexDeckM™

INTERIOR DECORATIVE DECK COVERING

Overview

SynDeck™ NuFlexDeckM™ system is an easy-to-apply system designed for interior decks and areas where a matte finish is desired. This is an epoxy deck leveling system with a low gloss urethane topcoat for ship passageways and wet spaces. This seamless decking can be installed in various colors, along with the option to add contrasting color flakes. It is designed to meet UK Def. Stan. and IMO requirements.

Approval

- IMO
- UK. Def. Stan.


Where to Use

- Passageways
- Wet Spaces / Showers

Benefits

- Ultra matte finish
- Seamless
- Waterproof system
- High build / self-leveling
- Vertical coves and slope to drains

System Layers



System Products


1. SynDeck™ Bond Coat SS1222
2. SynDeck™ Ultra Lightweight Underlayment SS1290FC
3. SynDeck™ Super Underlayment Sealer SS1259
4. SynDeck™ NuFlex Epoxy SS1286-XX
5. Color Flakes (optional)
6. SynDeck™ Clear Navy Epoxy SS5300
7. SynDeck™ Water Base Polyurethane Matte SS2450F

SYSTEM GUIDE

NuFlexDeckM™

INTERIOR DECORATIVE DECK COVERING


Standard Color Options



Tan




Scarlett Red




Cadet Silver



Deep Sea Blue



Pewter Grey



Arctic Ice Blue


Special and Custom Color Options



Midnight Blue



Brushed Nickel



Royal Blue



White



Blue Ash



Seafoam

Colors shown are approximate representations.
Actual results will vary.

Please contact your SynDeck™ representative for a full range of special and custom colors along with complete pricing and availability.

Available Tests

- MIL-PRF-32584 - Corrosion Resistance
- MIL-PRF-32584 - Impact Resistance
- ASTM F1914 - Indentation
- ASTM C579 - Compression Strength
- ASTM C580 - Flexural Strength of Mortars
- ASTM D4541 - Pull-Off Strength
- ASTM D523 - Gloss
- ASTM D2240 - Hardness
- ASTM D4060 - Abrasion
- ASTM D1894 - COF
- Moisture Absorption
- Resistance to Moisture and Temperature Changes